

ENVIROPRIMER WB

WATER-BASED PRIMER

DESCRIPTION

Enviroprimer WB is a water-based polymer emulsion primer designed to provide excellent adhesion of Envirosheet waterproofing membranes to structural substrates.

APPLICATIONS

Enviroprimer WB is designed to condition vertical and horizontal structural surfaces to which Envirosheet waterproofing membranes will be applied. These surfaces include structural concrete, masonry, wood, and metal.

Enviroprimer WB should only be used when the ambient and surface temperature is above 40°F (4°C).

PACKAGING

Enviroprimer WB is packaged in 5 gallon (18.9 liter) pails; 45 pails per pallet. Pail weight: 44-lbs. (20 kg).

INSTALLATION

Prior to application mix primer thoroughly. Apply by long nap roller or brush in an even film at 400 to 600 square feet per gallon (37 to 55 sq. meters per 3.78 liters). Allow primer to dry for 2 to 4 hours until it will not transfer when touched before applying waterproofing membrane. The primer must be completely dry to promote successful membrane installation. Envirosheet membrane will not adhere properly to uncured (wet) primer. High humidity or cool temperatures may require an over night cure. Reprime areas that do not receive waterproofing membrane within 24-hours.

Airless, air assist or air spray equipment may be also be used to apply the primer. Not suitable for garden type sprayer. Thoroughly mix primer before pouring into spray equipment. Spray primer over entire substrate. Enviroprimer WB is intended to be used as supplied and should not be diluted.

STORAGE

Store in protected area at temperatures above 50°F (10°C). Protect from freezing during shipping and storage. If product freezes discard it following applicable local, state, and federal regulations.

SAFETY

Workers should wear protective clothing and eye protection. Avoid eye and skin contact, particularly open cuts. In the event of contact, wash immediately. Do not ingest. Refer to MSDS for other warnings and product safety information.

TECHNICAL DATA

Color, Wet	White with blue tint
Color, Dry	Clear with blue tint
VOC Content	200 g/l
Solids Content	32% by weight
Flash Point	>200°F (93°C)
Adhesion to Concrete	7 lbs./lin.in. (min.) (1.23 kN/m)

MAY 2001 (Supersedes All Previous Versions)

The information contained herein supersedes all previous versions printed prior to May, 2001 and is believed to be accurate and reliable. CETCO makes no warranty of any kind and accepts no responsibility for the results obtained through application of this information. CETCO reserves the right to update information without notice.



Building Materials Group

1500 West Shure Drive Arlington Heights, IL 60004-1440 USA
tel (847) 392.5800 fax (847) 506.6195 <http://www.cetco.com>
(800) 527.9948