

1. Identification of Substance & Company

Product

Product name	Dermaprimer
HSNO approval	HSR002669
Approval description	Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006
UN number	1263
Proper Shipping Name	PAINT
DG class	3
Packaging group	II
Hazchem code	3YE
Uses	Bituminous solvent-based primer

Company Details

Company	Allco Waterproofing Solutions	
Address	5 Te Kia Place Albany Auckland New Zealand	PO Box 101-903 North Shore City 0745 New Zealand
Telephone	+64 9 448 1185	
Website	www.allco.co.nz	

Emergency Telephone Number: 021 441 329

2. Hazard Identification

Approval

This product has been approved under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002669, Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006), and is classified as follows:

Classes

Hazard Statements

3.1B	H225 - Highly flammable liquid and vapour.
6.1E (oral)	H303 - May be harmful if swallowed
6.1E (aspiration)	H304 - May be fatal if swallowed and enters airways.
6.3A	H315 - Causes skin irritation.
6.4A	H320 - Causes eye irritation.
6.7A	H350 - May cause cancer.
6.8B	H361 - Suspected of damaging fertility or the unborn child.
6.9B	H373 - May cause damage to organs through prolonged or repeated exposure.
9.1B	H411 - Toxic to aquatic life with long lasting effects.

SYMBOLS

DANGER



Other Classifications

There are no other Classifications that are known to apply.

Precautionary Statements

Precautionary Read label before use.
 Keep out of reach of children.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from ignition sources. No smoking.
 Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Wear protective gloves/eye/face protection.
 Wash hands thoroughly after handling.
 Do not breathe fume/vapours.
 Do not eat, drink or smoke when using this product.
 Avoid release to the environment.
 Collect spillage.
 IF exposed or concerned: Get medical advice/ attention.
 Store in a well-ventilated place. Keep cool.
 Store locked up.

Further precautionary statements can be found in Section 4 – First Aid.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
Bitumen	8052-42-4	47.5-50%
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	25-25.5%
Xylene	1330-20-7	9-10.5%
Toluene	108-88-3	8.5-10%
Tetrachloroethylene	127-18-4	4.5-5%
Methylene chloride	75-09-2	4.5-5%

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid

General Information

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service).

Recommended first aid facilities Ready access to running water is required. Accessible eyewash is required.

Exposure

Swallowed IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Apply continuous irrigation with water for at least 15 minutes holding eyelids apart. If eye irritation persists: Get medical advice.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: get medical advice/attention. Take off contaminated clothing and wash before re-use.

Inhaled IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Advice to Doctor

Treat symptomatically

5. Firefighting Measures

Fire and explosion hazards:	Vapours may form an explosive mixture in air which can be ignited by many sources such as pilot lights, open flames, electrical motors, switches and static electricity.
Suitable extinguishing substances:	Carbon dioxide, extinguishing powder, foam.
Unsuitable extinguishing substances:	Unknown.
Products of combustion:	Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures.
Protective equipment:	Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat and eye protection.
Hazchem code:	3YE

6. Accidental Release Measures

Containment	If greater than 1000L is stored, secondary containment and emergency plans to manage any potential spills must be in place. In all cases design storage to prevent discharge to stormwater.
Emergency procedures	In the event of spillage alert the fire brigade to location and give brief description of hazard. Stop the source of the leak, if safe to do so. Shut off all possible sources of ignition. Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain using sand, earth or vermiculite. Do not use sawdust. Prevent by whatever means possible any spillage from entering drains, sewers, or water courses. (If this occurs contact your regional council immediately).
Clean-up method	Use absorbent (soil, sand or other inert material). Rags are not recommended for the clean-up of spills, as they may create fire or environmental hazard. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.
Disposal	Mop up and collect recoverable material into labelled containers for recycling or salvage. Recycle containers wherever possible. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.
Precautions	Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation.

7. Storage & Handling

Storage	Avoid storage of harmful substances with food. Store out of reach of children. Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames. Avoid contact with incompatible substances as listed in Section 10. Location test certificates must be available if storing >100L (containers >5L), 250L (containers ≤5L), 50L (in use). Containers (and outer packaging) must bear the prescribed labelling, including the Hazchem code, UN number, flammability warning and name of contents.
Handling	Keep exposure to a minimum, and minimise the quantities kept in work areas. See section 8 with regard to personal protective equipment requirements. Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 10mg/m³ for dusts and mists when limits have not otherwise been established.

NZ Workplace Exposure Stds (2013)	Ingredient	WES-TWA	WES-STEL
	xylene	50ppm, 217mg/m ³	data unavailable
	tetrachloroethylene	50ppm, 335mg/m ³	150ppm, 1005mg/m ³
	toluene	50ppm, 188 mg/m ³ (skin)	data unavailable
	methylene chloride	50ppm, 174mg/m ³	data unavailable
	naphtha (petroleum), hydrodesulfurized heavy	100ppm, 525mg/m ³	data unavailable
	bitumen	5mg/m ³	data unavailable

* These workplace exposure standards are also Prescribed Exposure Standards (PES) under the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016.

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

Eyes



Avoid contact with eyes. Use safety glasses and or chemical splash goggles if splashes are possible.

Skin



Protective gloves are recommended. PVA or butyl rubber gloves are recommended. Replace frequently. Gloves should be checked for tears or holes before use.

Respiratory

A respirator when airborne concentrations approach the WES (section 8). Use a respirator with an organic vapour cartridge and a dust/mist filter. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order.

WES Additional Information

Not applicable

9. Physical & Chemical Properties

Appearance	black liquid
Odour	solvent odour
pH	no data
Vapour pressure	no data
Viscosity	no data
Boiling point	>70°C
Volatile materials	63.60%, 700g/L
Freezing / melting point	no data
Solubility	insoluble in water
Specific gravity / density	1.1 kg/L
Flash point	14°C
Danger of explosion	no data
Auto-ignition temperature	no data
Upper & lower flammable limits	no data
Corrosiveness	non corrosive

10. Stability & Reactivity

Stability	Stable, but can decompose in light.
Conditions to be avoided	Flammable substance. Keep away from sources of ignition at all times. Containers should be kept closed in order to avoid contamination. Keep out of direct sunlight.
Incompatible groups	Strong oxidisers, strong acids (e.g. sulphuric acid, nitric acid, perchloric acid), strong bases perchlorates, alkali and alkali earth metals, aluminium
Substance Specific Incompatibility	none known
Hazardous decomposition products	Oxides of carbon, hydrogen chloride, phosgene, chlorine and chlorine compounds, dioxins.
Hazardous reactions	none known

11. Toxicological Information

Summary

IF SWALLOWED: this mixture presents an aspiration hazard. The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

IF IN EYES: may cause irritation.

IF ON SKIN: may cause irritation.

IF INHALED: vapours may be irritating to the respiratory system.

CHRONIC TOXICITY: this mixture contains a known carcinogen (tetrachloroethylene) and a suspected carcinogen (methylene chloride). This mixture may also have a toxic effect on the central and peripheral nervous system, kidney, liver and heart. Exposure this mixture may also cause reproductive effect with toxicity and damage to a foetus.

Supporting Data

Acute	Oral	Using LD ₅₀ 's for ingredients, the calculated LD ₅₀ (oral, rat) for the mixture is between 2000 and 5000 mg/kg. Data considered includes: Xylene 1590 mg/kg (mouse), tetrachloroethylene 2600mg/kg (rat), toluene 636 mg/kg (rat), methylene chloride 1410 mg/kg (rat); 1600mg/kg (rat, oral), Naphtha (petroleum), hydrodesulfurized heavy >15000mg/kg (rat).
	Dermal	Using LD ₅₀ 's for ingredients, the calculated LD ₅₀ (dermal, rat) for the mixture is >5000 mg/kg. Data considered includes: Xylene >1700mg/kg, Naphtha (petroleum), hydrodesulfurized heavy >3160 mg/kg (rabbit).
	Inhaled	Using LC ₅₀ 's for ingredients, the calculated LC ₅₀ (inhalation, rat) for the mixture is >20mg/L (vapour). Data considered includes: Xylene 27.6 mg/L (rat, vapour), tetrachloroethylene 27mg/L (rat), toluene 12.5 - 28.8 mg/l (vapour, rat), methylene chloride 14400ppm/7h (mouse, inhalation); 52000mg/m ³ (rat, inhalation), Naphtha (petroleum), hydrodesulfurized heavy >12mg/L (rat).
	Eye	The mixture is considered to be an eye irritant. Xylene, tetrachloroethylene, toluene and methylene chloride are classed as eye irritant.
	Skin	The mixture is considered to be a skin irritant. Xylene, tetrachloroethylene, toluene, naphtha (petroleum) and methylene chloride are classedd as skin irritants.
Chronic	Sensitisation	No ingredient present at concentrations > 0.1% is considered a sensitizer.
	Mutagenicity	No ingredient present at concentrations > 0.1% is considered a mutagen.
	Carcinogenicity	The mixture is considered to be a known or presumed carcinogen. Tetrachloroethylene is classed as a known carcinogen. Methylene chloride is a suspected carcinogen.
	Reproductive / Developmental Systemic	The mixture is considered to be a suspected reproductive or developmental toxicant. Xylene and toluene are suspected of causing reproductive/developmental toxicity. The mixture is considered to be a suspected target organ toxicant. Xylene and toluene may affect the CNS. Tetrachloroethylene may affect the CNS, liver, heart and kidneys.
	Aggravation of existing conditions	None known.

12. Ecological Data

Summary

This mixture is considered toxic towards aquatic organisms with long lasting effects.

Supporting Data

Aquatic	Using EC ₅₀ 's for ingredients, the calculated EC ₅₀ for the mixture is between 1 mg/L and 10 mg/L and at least one of the components is either bioaccumulative or persistent in the aquatic environment. Data considered includes: Xylene 8.5mg/l (48hr, <i>Palaemonetes pugio</i> (Crustacea)), 3.3 mg/l (96hr, <i>Oncorhynchus mykiss</i>), 10mg/l (72hr, <i>Skeletonema costatum</i>), not bioaccumulative, readily biodegradable., tetrachloroethylene 0.2mg/L (72h, Algae), 4mg/L (96hr, Flagfish), 0.84mg/L (chronic, fathead minnow), 8.5mg/l (48hr, <i>Daphnia magna</i>), 0.4mg/L (21days, <i>Daphnia magna</i>). BCF: 25-8-77.1 (<i>Cyprinus carpio</i> , 56day), not degradable., toluene 5.8 mg/l (96hr, <i>Oncorhynchus mykiss</i>), 11.5 mg/l (48hr, <i>Daphnia magna</i>), 12.5mg/L (72hr, Algal), methylene chloride >100mg/L, Naphtha (petroleum), hydrodesulfurized heavy 2200mg/L (96hr, fish), 2.6 mg/L (96hr, Crustacea). No data for the mixture. Tetrachloroethylene log Ko/w >3.
Bioaccumulation	Tetrachloroethylen is not easily biodegradable.
Degradability	No evidence of soil toxicity.
Soil	Not considered as ecotoxic to terrestrial vertebrates. Using LD ₅₀ 's for ingredients, the calculated LD ₅₀ (oral, rat) for the mixture is >2000 mg/kg. See acute toxicity.
Terrestrial vertebrate	No evidence of toxicity towards terrestrial invertebrates.
Terrestrial invertebrate	no data
Biocidal	

13. Disposal Considerations

Restrictions	There are no product-specific restrictions, however, local council and resource consent conditions may apply, including requirements of trade waste consents.
Disposal method	Disposal of this product must comply with the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore rendered non-hazardous before discharge to the environment.
Contaminated packaging	Rinse containers with water before disposal. Preferably re-cycle container, otherwise send to landfill or similar.

14. Transport Information

Transport according to NZS 5433 (Transport of Hazardous Substances on Land). Considered a dangerous good for transport.

UN number:	1263	Proper shipping name:	PAINT
Class(es)	3	Packing group:	II
Precautions:	Flammable liquid	Hazchem code:	3YE

15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002669, Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006.

Specific Workplace Controls (as per HSNO approval referenced to Controls Matrix)

Key workplace requirements are:

SDS	To be available within 10 minutes in workplaces storing > any quantity.
Labelling	No removal of labels and/or decanting of product into other containers can occur.
Emergency plan	Required if > 1000L is stored.
Approved handler	Required if >10L is stored or used.
Tracking	Not required.
Bunding & secondary containment	Required if > 1000L is stored.
Signage	Required if > 250L is stored.
Location test certificate	Required if > 100L (containers >5L), 250L (containers ≤5L), 50L (in use) is stored in any one location.
Flammable zone	Must be established if > 100L (closed containers), 25L (decanting), 5L (open occasionally), 1L (in use), stored in any one location is stored in any one location.
Fire extinguisher	If > 250L present.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

16. Other Information

Abbreviations

Approval Code	Approval HSR002669, Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006 Controls, EPA. www.epa.govt.nz
CAS Number	Unique Chemical Abstracts Service Registry Number
Ceiling	Ceiling Exposure Value: The maximum airborne concentration of a biological or chemical agent to which a worker may be exposed at any time.
Controls Matrix	List of default controls linking regulation numbers to Matrix code (e.g. T1, I16).
EC₅₀	Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test population (e.g. daphnia, fish species)
EPA	Environmental Protection Authority
HAZCHEM Code	Emergency action code of numbers and letters that provide information to emergency services, especially fire fighters
HSNO	Hazardous Substances and New Organisms (Act and Regulations)
IARC	International Agency for Research on Cancer
LEL	Lower Explosive Limit
LD₅₀	Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).
LC₅₀	Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population (usually rats)
MSDS (SDS)	Material Safety Data Sheet (or Safety Data Sheet)
PES	Prescribed Exposure Standard means a WES or a biological exposure standard that is prescribed in a regulation, a safe work instrument or an approval under HSNO (including group standards).
STEL	Short Term Exposure Limit - The maximum airborne concentration of a chemical or biological agent to which a worker may be exposed in any 15 minute period, provided the TWA is not exceeded
TWA	Time Weighted Average – generally referred to WES averaged over typical work day (usually 8 hours)
UEL	Upper Explosive Limit
UN Number	United Nations Number
WES	Workplace Exposure Standard - The airborne concentration of a biological or chemical agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring using procedures that gather air samples in the worker's breathing zone.

References

Data	Unless otherwise stated comes from the EPA HSNO chemical classification information database (CCID).
EPA Transfer Gazettes	Classifications and controls assigned for specific ingredients (consolidated gazette, 2004)
WES 2013	The NZ Workplace Exposure Standards Effective from 2013, published by WorkSafe NZ and available on their web site – www.worksafe.govt.nz .
WES 2002	Workplace Exposure Standards published by the Occupational Safety and Health Service, Department of Labour, January 2002, ISBN 0-477-03660-0. These are the WES referred to under the Group Standard (HSNO approval) and may constitute a PES.
Other References:	Suppliers SDS

Review

Date	Reason for review
June 2016	Not applicable – new SDS

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely HSNO classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 9 940 30 80.

