



NOTE  
ALLCO WATERPROOFING SUGGESTS  
THAT ROOF DRAINAGE BE DESIGNED TO  
USE CLAMPED DRAINAGE OUTLETS IN  
PREFERENCE TO SCUPPER OUTLETS

NOTE  
Z= VARIABLE ACCORDING TO WIND  
ZONES, REFER TO NZBC E2 AS1 TABLE 7  
(70mm TYPICAL)

STRIP OF BASE SHEET  
MEMBRANE TO REBATE IN  
SUBSTRATE

NOTE - RADIUS EDGES TO  
SUSTRATE - 5MM MIN.

CASALI CAP SHEET  
MEMBRANE

CASALI BASE SHEET  
MEMBRANE

PRIMER  
(DERMAPRIMER OR IDROPRIMER)

TIMBER FILLET

SUBSTRATE  
BY DESIGN.

STRIP OF BASE SHEET MEMBRANE TO  
REBATE IN SUBSTRATE

PREFINISHED  
PARAPET FLASHING  
BY OTHERS

SUBSTRATE /  
CLADDING BY  
DESIGN.

RAINWATER HEAD

FLASHING TAPE LAPS TO  
SCUPPER PENETRATION  
- BY BUILDER

FABRICATED METAL  
RAINWATER HEAD



The information and data contained herein are believed to be accurate and reliable.  
This information does not constitute a warranty and should be used in conjunction with  
the project specification document supplied by Allco Waterproofing Solutions Ltd  
Please contact Allco Waterproofing Solutions Ltd with any questions or deviations from  
this information.  
© Allco Waterproofing Solution Ltd

For Technical Advice Contact:  
Web: [www.allco.co.nz](http://www.allco.co.nz)  
Email: [info@allco.co.nz](mailto:info@allco.co.nz)  
Telephone: 09 448 1185  
Facsimile: 09 448 1186



DRAWN BY:  
ALLCO

DATE:  
17/04/19

DRAWING REF:  
CA-012

REV:  
1